



Equipment Needed to Plug a 6" Gas Main to 285 psi


Technical Datasheet Date: May 2021





6" Gas Main to 285 psi






Note: Consult your TDW representative for additional fitting options.




Equipment Needed to Plug a 8" Gas Main to 285 psi





8" Gas Main to 285 psi






Note 1:* 8-inch Spool Adapter required to set 8-inch SHORTPLUG™ with Guide Bars in SHORTSTOPP Type II 3-Way™ Tee fittings using the 06-1544-0000 Adapter.

Note 2: Consult your TDW representative for additional fitting options.



Equipment Needed to Plug a 10" Gas Main to 285 psi

*10" applications use 12" equipment



completion plug and O-ring)


completion plug and tee.



10" Gas Main to 285 psi



See Bulletin 2110.001




Note 1: *12-inch Spool Adapter required to set 10-inch SHORTPLUG™ with Guide Bars in SHORTSTOPP Type II 3-Way™ Tee fittings using the 06-1546-0000 Adapter and 07-1586-0000 Completion Machine

Note 2: Consult your TDW representative for additional fitting options.




Equipment Needed to Plug a 12" Gas Main to 285 psi





12" Gas Main to 285 psi





Note 1: Consult your TDW representative for additional fitting options.

Note 2: *The 07-1586-0000 Completion Machine with 48" travel is required to set 12" SHORTPLUGTM with Guide Bars in SHORTSTOPP Type II 3-WayTM Tee fittings using the 06-1546-0000 Adapter.