
Tapping and ProStopp™ DS



Equipment Needed to Plug a 6" Gas Main to 300 psi


Technical Datasheet Date: July 2021





6" Gas Main to 300 psi






Note: Consult your TDW representative for additional fitting options.

Tapping and ProStopp™ DS




Equipment Needed to Plug a 8" Gas Main to 300 psi





8" Gas Main to 300 psi





Note 1:* 8-inch Spool Adapter required to set 8-inch SHORTPLUG™ with Guide Bars in SHORTSTOPP Type II 3-Way™ Tee fittings using the 06-1544-0000 Adapter.


Note 2: Consult your TDW representative for additional fitting options.

TDW

Tapping and ProStopp™ DS

Equipment Needed to Plug a 10" Gas Main to 300 psi

*10" applications use 12" equipment






10" Gas Main to 300 psi



See Bulletin 2110.001




Note 1: *12-inch Spool Adapter required to set 10-inch SHORTPLUG™ with Guide Bars in SHORTSTOPP Type II 3-Way™ Tee fittings using the 06-1546-0000 Adapter and 07-1586-0000 Completion Machine

Note 2: Consult your TDW representative for additional fitting options.

Tapping and ProStopp™ DS




Equipment Needed to Plug a 12" Gas Main to 300 psi





12" Gas Main to 300 psi





Note 1: Consult your TDW representative for additional fitting options.

Note 2: *The 07-1586-0000 Completion Machine with 48" travel is required to set 12" SHORTPLUGTM with Guide Bars in SHORTSTOPP Type II 3-WayTM Tee fittings using the 06-1546-0000 Adapter.